MAXHUB 01

Commercial Display

Product Model ND55CMA

Taking simplicity, safety and flexibility to new levels. MAXHUB Commercial Display makes every organization more effective and productive.





Professional 4K Display

4K Resolution
Anti-Glare, 25% Haze



Wireless Screen Sharing

Share your screen through MAXHUB
Share app or wireless dongle



External Control

Display Control through IP or RS232 protocol



Device Management

Manage through cloud based MAXHUB PIVOT



Built-in Speakers

2x 10W



Conformal Coating

Commercial level design of hareware



Energy Saving

ErP Certified
Energy Star 8.0 Certified

Display	
Screen Size (class)	55"
Diagonal	54.6" 138.7cm
Panel Type	VA
Haze	25% (Anti-Glare)
Aspect Ratio	16:9
Native Resolution	3840*2160
Refresh Rate	60Hz
Brightness (Typ.)	450 nits
Backlight Type	Direct Lit
Contrast Ratio	4000:1
Viewing Angle (H x V)	$178^{\circ} (H/V)$
Response Time	6.5ms
Life Time (Min.)	≥50,000 hours
Operation Hours (Hours / Day)	16/7
Orientation	Portrait / Landscape

A55 x4
Mali-G52 x2
4G
32G
Android 11.0
4K

Connectivity	
Input	HDMI in 2.0 x2 USB Type-C x1 (PD 65W) USB Type-A 3.0 x1 (for external peripherals) USB Type-A 2.0 x1 (only for firmware upgrade) RJ45 in x1
Output	HDMI out 2.0 x1 SPDIF x1 (Optical) Audio out x1 (3.5mini jack)
External Control Wi-Fi	RS232 x1 / IR Receiver Removable Wi-Fi Module Wi-Fi 6 Support 2.4G&5G 802.11ac/b/g/n/a/ax
OPS Slot	No

Mechanical Specification	
Bezel Width (L x R x T x B)	9.9 / 9.9 / 9.9 / 9.9 mm 0.39 / 0.39 / 0.39 / 0.39 inch
Product Dimension (W x H x D)	$1233 \times 703.5 \times 71.4 \text{ mm}$ $48.54 \times 27.7 \times 2.81 \text{ inch}$
Package Dimension (W x H x D)	1332 × 819 x 156 mm 52.44 x 32.24 x 6.14 inch
Product Weight (Net)	13.40 kg / 29.54 pounds
Package Weight (Gross)	19.5 kg / 43 pounds
VESA Mount (mm)	400×200
Handle	No

Environmental Conditions	
Operation Temperature	0° C ~ 40° C
Operation Humidity	10% ~ 90%RH
Storage Temperature	-20° C ~ 60° C
Storage Humidity	10% ~ 90%RH
Power	
Power Supply	100-240V~50/60Hz
Power Consumption (Typical)	150W
Power Consumption (Max)	250W
Sound	
Speaker Power Output	2 x 10W
Certification	
Safety	IEC 62368-1
EMC	Class B
ErP	Yes
Energy Star	Yes
Features	
Built-In Media Player	Yes
Device Management System	Maxhub PIVOT
Screen Share	MAXHUB Share

Power Cord, Wi-Fi Module x1, HDMI Cable (2m 6.56feet) x1 , Remote Control x1, Wall Mount x1	
d (ST41B) Mobile Sta	and (ST23C)
n	nd (ST41B) Mobile Sta









