



## User Manual

4K Scaler Switcher Multiformat Scaling, 4K (60Hz 4:2:0), HDMI & HDBaseT Out

### Model PT-PSW-92

Designed in Germany

## Preface

Read this user manual carefully before using the product. Pictures shown in this manual are for reference only. Different model layouts and specifications are subject to the physical product.

This manual is for operation instructions only, not for any maintenance usage.

In the constant effort to improve our product, we reserve the right to make changes in functions or parameters without prior notice or obligation.

## Trademarks

Product model and logo are trademarks. Any other trademarks mentioned in this manual are acknowledged as the properties of the trademark owner. No part of this publication may be copied or reproduced without the prior written consent.

## FCC Statement

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. It has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a commercial installation.

Operation of this equipment in a residential area is likely to cause interference, in which case the user at their own expense will be required to take whatever measures may be necessary to correct the interference.

Any changes or modifications not expressly approved by the manufacture would void the user's authority to operate the equipment.



## REACH | 1907/2006/EU

## ROHS | 2011/65/EU

PureLink hereby declares that this product **PureTools PT-PSW-92** complies with Directives 1907/2006/EU und 2011/65/EU.

## EMC / LVD (Electro Magnetic Compatibility / Low Voltage Directive)

PureLink GmbH hereby declares that this product **PureTools PT-PSW-92** complies with Directives 2014/30/EU and 2014/35/EU. The full text of the EU Declaration of Conformity is available at the following Internet address:

[http://www.purelink.de/ce/4251364706855\\_CE.pdf](http://www.purelink.de/ce/4251364706855_CE.pdf)



## SAFETY PRECAUTIONS

To insure the best from the product, please read all instructions carefully before using the device. Save this manual for further reference.

- Unpack the equipment carefully and save the original box and packing material for possible future shipment.
  - Follow basic safety precautions to reduce the risk of fire, electrical shock and injury to persons.
  - Do not dismantle the housing or modify the module. It may result in electrical shock or burn.
  - Using supplies or parts not meeting the products' specifications may cause damage, deterioration or malfunction.
  - Refer all servicing to qualified service personnel.
  - To prevent fire or shock hazard, do not expose the unit to rain, moisture or install this product near water.
  - Do not put any heavy items on the extension cable in case of extrusion.
  - Do not remove the housing of the device as opening or removing housing may expose you to dangerous voltage or other hazards.
  - Install the device in a place with fine ventilation to avoid damage caused by overheat.
  - Keep the module away from liquids.
  - Spillage into the housing may result in fire, electrical shock, or equipment damage. If an object or liquid falls or spills on to the housing, unplug the module immediately.
  - Do not twist or pull by force ends of the optical cable. It can cause malfunction.
  - Do not use liquid or aerosol cleaners to clean this unit. Always unplug the power to the device before cleaning.
  - Unplug the power cord when left unused for a long period of time.
  - Information on disposal for scrapped devices: do not burn or mix with general household waste, please treat them as normal electrical wastes.
-

---

## Contents

1. Introduction .....	1
1.1 Introduction to PT-PSW-92 .....	1
1.2 Feature .....	1
1.3 Package List .....	2
2. Panel Description .....	3
2.1 Front Panel .....	3
2.2 Rear Panel .....	4
3. System Connection .....	6
3.1 Usage Precaution .....	6
3.2 System Diagram .....	6
3.3 Microphone Connection .....	7
4. Button Control .....	10
4.1 Manual Switching .....	10
4.2 Auto Switching .....	10
4.3 Volume Adjustment .....	11
5. IR Control .....	12
5.1 IR Remote Control .....	12
5.2 IR Pass-through Control .....	13
5.2.1 To Control Far-end Source/Display .....	13
5.2.2 To Control Local Source/PT-PSW-92 .....	14
6. RS232 Control .....	15
6.1 RS232 Connection .....	15
6.2 RS232 Control Software .....	15
6.3 RS232 Command .....	17
7. GUI Control .....	20

---

7.1 Control Menu.....	21
7.2 Volume Menu .....	22
7.3 Configuration Menu .....	23
7.4 Password Menu .....	26
7.5 GUI Update .....	27
8. OSD Control .....	28
9. Specification.....	29
10. Panel Drawing.....	31
11. Troubleshooting & Maintenance .....	32
12. After-Sales Service .....	33

## 1. Introduction

### 1.1 Introduction to PT-PSW-92

The PT-PSW-92 is a 9 inputs multi format A/V presentation auto 4k Scaler Switcher that scales video signals to HDMI and HDBaseT outputs simultaneously. The HDBaseT output supports PoH and can connect to a compatible HDBaseT Receiver up to a maximum of 100 meters / 328 feet.

With 1 IR ALL IN and 1 IR ALL OUT, the IR control signals can be transmitted bi-directionally between the PT-PSW-92 and compatible HDBaseT Receiver (such as PT-HDBT-1001-RX) or HDBaseT Transmitter.

The PT-PSW-92 can be controlled either by front panel buttons, IR Remote, RS232 or GUI. With a microphone input that supports phantom power and a balanced stereo audio output for audio reinforcement, the PT-PSW-92 can handle a myriad of A/V applications.

### 1.2 Feature

- Compliant with HDMI2.0& HDCP2.2.
- Supports video source auto-switching function.
- HDBaseT input with distances up to 230 ft (70m) at 1080p and 131 ft (40m) at 4Kx2K on a single CAT5e/6/7 cable.
- HDBaseT output with distances up to 328 ft (100m) at 1080p and 230ft (70m) at 4Kx2K on a single CAT5e/6/7 cable.
- Output resolutions selectable to assure preferred output, and supports various output resolutions, such as 1280x720(default), 1920x1080, 1024x768, 3840x2160@30Hz, 3840x2160@60Hz.
- DP, HDMI and VGA video inputs can be embedded with external audio.
- Support Line or Mic audio inputs, and MIC port supports balance/unbalance signal, suppress the external noise effectively.

- Controllable via buttons, IR Remote, RS232 & GUI.
- Powerful OSD function.
- Bi-directional IR & RS232 pass-through.
- Supports online software upgrading.

### 1.3 Package List


Scaler Switcher	<ul style="list-style-type: none"><li>• 1 x PT-PSW-92 Scaler Switcher</li><li>• 2 x Mounting Ears with 4 Screws</li><li>• 4 x Plastic Cushions</li><li>• 1 x IR Remote</li><li>• 1 x IR Receiver</li><li>• 1 x IR Emitter</li><li>• 6 x 3-Pin Phoenix Connectors</li><li>• 1 x 5-Pin Phoenix Connector</li><li>• 1 x Power Cord</li></ul>
HDBaseT Receiver	<ul style="list-style-type: none"><li>• 1 x TPUHPT-HDBT-1001-RX HDBaseT Receiver</li><li>• 2 x Mounting Ears with 4 Screws</li><li>• 4 x Plastic Cushions</li></ul>
	<ul style="list-style-type: none"><li>• 1 x User Manual</li></ul>

**Note:** Please contact your distributor immediately if you found any damage or defect in the components.




## 2. Panel Description

### 2.1 Front Panel



- ① Power Indicator:
  - Off when there is no power to the device.
  - Green when the device is in standby mode.
  - Red when the device is powered on.
- ② Auto switching mode selector and activity LED
- ③ 1-HDBT input selector and activity LED
- ④ 2-DP input selector and activity LED
- ⑤ 3-HDMI input selector and activity LED
- ⑥ 4-HDMI input selector and activity LED
- ⑦ 5-HDMI input selector and activity LED
- ⑧ 6-HDMI input selector and activity LED
- ⑨ 7-HDMI input selector and activity LED
- ⑩ 8-VGA input selector and activity LED
- ⑪ 9-VGA input selector and activity LED
- ⑫ OUTPUT BACK/720P: Press this to let the display be black screen or long-press for 3 seconds to reset the output resolution to 1280×720p.
- ⑬ MUTE: Press this to mute output.
- ⑭ Volume Knob  
Press this knob to select AMP (amplifier), SOURCE or MIC audio input, and then turn the knob to adjust the volume.

## 2.2 Rear Panel



### INPUTS:

- ① 1-HDBT/PoH& RS232:
  - HDBaseT input port: support PoH, connect with an HDBaseT Transmitter to receive AV signal or IR/RS232 control signal.
  - The RS232 port and that one on HDBaseT Transmitter can transmit RS232 commands each other by pass-through function.
- ② 2-DP: DP input with external audio input.
- ③ 3-HDMI: HDMI input port with external audio input, support 4k@60Hz 4:4:4, HDCP 2.2.
- ④ 4-HDMI-7-HDMI: 4 HDMI input ports, support 4k@60Hz 4:4:4, HDCP 2.2.
- ⑤ 8-VGA-9-VGA: 2 VGA input ports with VGA auxiliary audio inputs.
- ⑥ LINE: Line audio input port.
- ⑦ MIC: MIC audio input port. DIP switch for selecting the below 3 mode:
  - 48V phantom power mode (connect with condenser microphone).
  - MIC mode (connect with dynamic microphone).
  - LINE mode (connect with wireless microphone or line audio).

**OUTPUTS:**

- A. HDMI: HDMI video output port.
- B. HDBT/PoH: Support PoH. Connect with an HDBaseT Receiver to transmit AV signal or IR/RS232 control signal.
- C. AUDIO: Audio output port, the audio comes from the input audio corresponding to the selected video source and is mixed with MIC audio.
- D. RS232: The RS232 port and that one on HDBaseT Receiver can transmit RS232 commands each other by pass-through function.

**CONTROL:**

- a. FIRMWARE: Type-A USB port for updating system firmware or loading customized EDID data.
- b. IR EYE: Connect with IR Receiver (with carrier wave only) to receive IR signal send by IR Remote to control this Scaler Switcher.
- c. IR ALL IN: IR input port used with far-end IR output port. Connect with IR Receiver (with carrier) to receive IR signal from all kinds of IR Remote to control far-end devices from local.
- d. IR ALL OUT: IR output port used with far-end IR input port. Connect with IR emitter (with carrier) to send IR signal to control local devices from remote.
- e. RS232: Serial port, 3-pin phoenix connector, connect with a control device (such as PC) to control PT-PSW-92.
- f. TCP/IP: Ethernet port, connect PC to control PT-PSW-92 via GUI.

I: AUDIO AMP: Audio output port, connect with 70V/100V constant voltage audio amplifier.


II: AC100V-240V: Power port, connect to an AC 100V-240V power via the included power cord.

## 3. System Connection

### 3.1 Usage Precaution

- Verify all components and accessories included before installation.
- System should be installed in a clean environment with proper temperature and humidity (see page29 for limits).
- All of the power switches, plugs, sockets and power cords should be insulated and safe.
- All devices should be connected before power on.

### 3.2 System Diagram



### 3.3 Microphone Connection


PT-PSW-92 provides with one 3-level microphone input port, to accommodate different microphone input modes, including 48V phantom power mode, MIC mode & LINE mode.

#### ➤ 48V phantom power Mode

48V phantom power input has a good frequency characteristic, high input impedance and high sensitivity.

When switching to "48V", the MIC input will provide a 48V phantom power. This is only used for **condenser microphone**.

Connect the microphone in this way: "+" connects to positive, "-" connects to negative and "⏏" to ground.



#### ➤ MIC Mode


MIC input has a low frequency characteristics, and wide frequency response.

When switch to "MIC", the microphone input is used for connecting with **dynamic microphone**. There are two different connection methods:


##### ① Unbalanced connection:

"+" and "⏏" connect to ground, and "-" connects to signal.

"-" and "⏏" connect to ground, and "+" connects to signal.



- ② Balanced connection: "+" connects to positive, "-" connects to negative and "⏏" connects to ground.



➤ **LINE Mode**


LINE input has a low frequency characteristics, and wide frequency response.

When switch to "LINE", the microphone input is used for connecting with line audio or wireless microphone output. There are two different connection methods:


① Unbalanced connection:

"+" and "⊥" connect to ground, and "-" connects to signal.

"-" and "⊥" connect to ground, and "+" connects to signal.



② Balanced connection: "+" connects to positive, "-" connects to negative and "⊥" connects to ground.



## 4. Button Control

Front panel buttons can be used for switching operations and volume adjusting.

### 4.1 Manual Switching

Press **1-HDBT/PoH**, **2-DP**, **3-HDMI**, **4-HDMI**, **5-HDMI**, **6-HDMI**, **7-HDMI**, **8-VGA**, or **9-VGA** on front panel to select the corresponding input source.

### 4.2 Auto Switching

Press **AUTO** to enter in auto-switching mode.

The auto-switching mode abides by the following principles:

- **New input**  
Once detecting a new input signal, the switcher would switch to this new signal automatically.
- **Rebooting device**  
PT-PSW-92 have the ability to save the last configuration before losing power. If the last switching mode is auto-switching, once rebooted, the switcher will automatically enter auto-switching mode, then detect all inputs and memorize their connection status for future rebooting using. If the last displayed signal is still available, the unit will output the signal. If not, the unit will detect all the input signals with priority from 1-HDBT/PoH to 9-VGA. When detected the first signal, it will transfer to output.
- **Signal removal**  
Once removing the current display signal, PT-PSW-92 will detect all input signals with priority from 1-HDBT/PoH to 9-VGA. It will transfer the signal firstly detected to be available to output devices.



**Note:**

- *When the DP signal is switched as input, the DP source device may not read the EDID data from display device, at this point re-plug the DP source device to solve this phenomenon.*
- *Auto-switching function works only when inputting new signal, removing a signal or power rebooting.*


## 4.3 Volume Adjustment

Press **Volume Knob** to choose AMP, SOURCE or MIC audio needed to be adjusted, the corresponding LED will turn green and keep on, and then adjust the Volume Knob to increase or decrease sound volume.

## 5. IR Control

### 5.1 IR Remote Control

Connect IR Receiver to the **IR EYE** port, PT-PSW-92 can be controlled by using the IR Remote as below.



- ① Enter/ exit standby mode.
- ② Input channel selection buttons (1~9): Select video source via pressing corresponding button (audio switched following the corresponding 2-DP/3-HDMI/8-VGA/9-VGA).
- ③ Auto: Enter/Exit auto-switching mode.
- ④ OK: confirm button; Navigation buttons: UP/DWON/LEFT/ RIGHT button, for value setting or page-turn.
- ⑤ VOL: Volume adjusting button. After pressing this button, the volume adjusting menu will be showed on Display, and then press UP/DOWON button to increase/decrease volume.
- ⑥ Mute/ unmute audio.
- ⑦ Exit button: Exit OSD menu or current operation.
- ⑧ Enter OSD menu or used to return to previous menu.


#### Important notice:

- Please use this IR Remote carefully.
- Please wipe the surface using clean towels or absorbent soft cloth.
- To reduce the risk of fire or electric shock do not expose this apparatus to rain or moisture.



### 5.2.2 To Control Local Source/PT-PSW-92


Connect an IR emitter to IR ALL OUT port on the PT-PSW-92, and then connect IR Receiver to the IR IN ports on the HDBaseT Transmitter and Receiver, the source devices or PT-PSW-92 can be control by their IR Remote.



## 6. RS232 Control

### 6.1 RS232 Connection

Connect the control PC to the RS232 port as shown as below:



The baud rate support 2400, 4800, 9600(default), 19200, 38400, 57600 or 115200.

### 6.2 RS232 Control Software

- **Installation** Copy the control software file to the computer connected with PT-PSW-92.
- **Uninstallation** Delete all the control software files in corresponding file path.
- **Basic Settings:**


First to connect PT-PSW-92 with all input devices and output devices needed, then to connect it with a computer which is installed with RS232 control software.

Double-click the software icon to run this software.

Here we take the software **CommWatch.exe** as example. The icon is showed as below:



The interface of the control software is showed as below:



Please set the parameters of COM number, bound rate, data bit, stop bit and the parity bit correctly, and then you are able to send command in Command Sending Area.

## 6.3 RS232 Command

**Communication protocol:** RS232 Communication Protocol

Baud rate: 9600

Data bit: 8

Stop bit: 1

Parity bit: none

Command	Function	Feedback
Update	Software update.	update
Factory	Reset to factory default.	Factory reset
Menu	Open OSD menu.	Key menu
Up	UP button.	Key up
Down	DOWN button.	Key down
Left	LEFT button.	Key left
Right	RIGHT button.	Key right
Exit	EXIT button (exit OSD).	Key exit
Ok	OK for OSD selection.	Key ok
Hdbtin	Switch to 1-HDBT input.	Port 1
Dpin	Switch to 2-DP input.	Port 2
Hdmi3	Switch to 3-HDMI input.	Port 3
Hdmi4	Switch to 4-HDMI input.	Port 4
Hdmi5	Switch to 5-HDMI input.	Port 5
Hdmi6	Switch to 6-HDMI input.	Port 6
Hdmi7	Switch to 7-HDMI input.	Port 7
VGA8	Switch to 8-VGA input.	Port 8
VGA9	Switch to 9-VGA input.	Port 9
4k2k60	Set output resolution to 4Kx2K@60Hz.	4k2k60
4k2k30	Set output resolution to 4Kx2K@30Hz.	4k2k30

Command	Function	Feedback
108060	Set output resolution to 1080p@60Hz.	108060
1280720	Set output resolution to 1280x720.	1280720
1024768	Set output resolution to 1024x768.	1024768
1360768	Set output resolution to 1360x768.	1360768
Redid	Restore the default EDID.	RestoreEDID
Setedid	Read the EDID from output.	xxxxxx...
DP audio1	Select embedded audio input for 2-DP video signal.	DP audio embedded
DP audio2	Select external audio input for 2-DP video signal.	DP audio external
HDMI audio1	Select embedded audio input for 3-HDMI video signal.	HDMI audio embedded
HDMI audio2	Select embedded audio input for 3-HDMI video signal.	HDMI audio external
Ampadd	Increase the volume of AMP audio.	amp volume: xx
Ampin	Decrease the volume of AMP audio.	amp volume: xx
Sourceadd	Increase the volume of source audio.	source volume: xx
Sourcemin	Decrease the volume of source audio.	source volume: xx
Micadd	Increase the volume of MIC.	mic volume: xx
Micmin	Decrease the volume of MIC.	mic volume: xx
Micmute	Mute MIC audio.	Micmute
Micunmute	Unmute MIC audio.	Micunmute
Sourcemute	Mute SOURCE audio.	Sourcemute
Sourceunmute	Unmute SOURCE audio.	Sourceunmute
Ampmute	Mute AMP audio.	Ampmute
Ampunmute	Unmute AMP audio.	Ampunmute




Command	Function	Feedback
Output?	Inquire the output resolution.	4k2k60/4k2k30/1280720/1024768/1360768
Audio?	Inquire the input audio type.	HDMI external HDMI embedded DP external DP embedded
Input?	Inquire the input source.	Hdvt/Dp/Hmdi3/Hmdi4/ Hmdi5/Hmdi6/Hmdi7/ Vga8/Vga9
Volume?	Inquire audio volume.	amp volume: xx source volume: xx mic volume: xx Mute/Unmute
Svol:xx	Set the volume of source audio.	source volume: xx
Avol:xx	Set the volume of AMP audio.	amp volume: xx
Mvol:xx	Set the volume of MIC audio.	mic volume: xx

## 7. GUI Control


In addition to control PT-PSW-92 via front panel button, IR Remote and RS232 communication software. PT-PSW-92 can be controlled via GUI. It allows users to interact with PT-PSW-92 through graphical icons and visual indicators.

Type **192.168.0.178** in your browser, it will enter the log-in interface shown as below:



## 7.1 Control Menu

Type user name: user and password: user (default setting) on the log-in interface, and then click **Login** to enter Control menu shown as below:



- **Source:** Click the corresponding button (**1-HDBT**, **2-DP**, **3-HDMI**, **4-HDMI**, **5-HDMI**, **6-HDMI**, **7-HDMI**, **8-VGA** or **9-VGA**) to select video input source, or click **AUTO** to enter auto-switching mode.
- **Audio:** Click **2-DP** or **3-HDMI** to select external audio for DP or HDMI video signal.
- **Black:** Click this to output black screen for display.


## 7.2 Volume Menu


Click **Volume** to enter volume menu shown as below:



- The volume of Source, MIC, and Line audio can be adjusted.

## 7.3 Configuration Menu

① Click  on control menu to enter setting menu shown as below:



- **Output Resolution:** Select the output resolution that you need and then click **Confirm** to save setting.
- **Update:** Insert the USB flash disk with EDID file/software updating file to FIRMWARE port, and then click EDID/Firmware to start update procedure.

- ② Click **Network** to enter network setting menu shown as below:

Configuration Password

Setting Network Source Label

MAC Address: AC-A2-13-98-41-79

DHCP  Static IP

IP Address: 192.168.0.178

Subnet Mask: 255.255.255.0


Gateway: 192.168.0.1

Confirm

PureLink  
digital solutions

- Dynamic or static IP mode can be selected. Under static IP mode, IP address and subnet mask, gateway can be set and make sure the IP addresses are different to avoid IP conflict.


- ③ Click **Source Label** to enter source label setting menu shown as below:



- The name of source input selection button can be modified as you need.

## 7.4 Password Menu

Click **Password** on the top of interface to enter password menu shown as below:




The screenshot shows the 'Password' menu in the PureTools interface. The interface has a dark blue background with a lighter blue header bar. The header bar contains two tabs: 'Configuration' and 'Password'. The 'Password' tab is selected. Below the header, there is a section titled 'Credentials' with a horizontal line above and below it. Under 'Credentials', there are two password fields: 'Admin Password:' with the value 'admin' and 'User Password:' with the value 'user'. Below the password fields, there is a section titled 'Version' with a horizontal line above and below it. Under 'Version', there are two lines of text: 'GUI: V1.0.1' and 'Firmware: V1.0.0'. At the bottom center of the main content area, there is a 'Confirm' button. At the bottom left of the interface, there is a back arrow icon. At the bottom right, there is the 'PureLink digital solutions' logo.

- Admin/user password can be modified as you need.



## 7.5 GUI Update

GUI for PT-PSW-92 supports online update in <http://192.168.0.178:100>. Type the username and password (the same as the GUI log-in settings, modified password will be available only after rebooting) to log in the configuration interface. After that, click **Administration** at the source menu to get to **Upload Program** as shown below:




Select the desired update file and press **Apply**, it will start upgrading then.

## 8. OSD Control

PT-PSW-92 provides a powerful OSD operation menu, contains 3 parts: optional settings, image settings, and system setting etc.

There are two ways to enter OSD menu:


- ① Press the MENU button  on IR Remote.
- ② Send the command Menu on RS232 Control Software.

### Operation:

- Press direction buttons on IR Remote to switch between menu options and menu pages.
- Press **OK** on the IR Remote to confirm the selection.

### OSD MENU-SETUP

Including Picture Mode Standard, Color Mode, Zoom Mode, Restore Default, Software Update.




## 9. Specification

Video	
Video Input	(1) HDBaseT;(1) Display Port; (5) HDMI; (2) VGA
Video Input Connector	(1) RJ45; (1) Female Display Port; (5) Type A HDMI; (2) 15-pin Female VGA
Video Output	(1) HDMI; (1) HDBaseT
Video Output Connector	(1) Type A HDMI; (1) RJ45
Output Resolution	1280x720 (default), 1920x1080, 1024x768, 3840x2160@30Hz, 3840x2160@60Hz
Standards	Input video support HDMI 2.0 & HDCP2.2; Output video support HDMI 2.0 & HDCP1.4.
Audio	
Audio Input	(1) Stereo Audio Input for 2-DP; (1) Stereo Audio Input for 3-HDMI; (2) Stereo Audio Inputs for 8-VGA and 9-VGA; (1) LINE Audio; (1) MIC Audio
Audio Input Connector	(4) 3.5mm Stereo Jacks; (2) 3-pin Phoenix Connector
Audio Input Impedance	>10kΩ
Audio Output	(1) Dual-Mono Analog Audio; (1) Power Amplifier with Fixed Voltage
Audio Output Connector	(1) 5-pin Phoenix Connector; (1) 3-pin Phoenix Connector
Audio Output Impedance	70Ω
Frequency Response	20Hz~20K Hz
Stereo Channel Separation	>80dB @1KHz
Control Part	
Control Port	(1) FIRMWARE; (1) IR EYE; (1) IR ALL IN; (1) IR ALL OUT; (3) RS232; (1) TCP/IP
Control Connector	(1) Type-A USB (3) 3.5mm Mini Jacks; (3) 3-pin Phoenix Connectors; (1) RJ45
General	
Transmission Distance	HDBaseT Input: 1080p≤70m, 4Kx2K≤40m; HDBaseT Output: 1080p≤100m, 4Kx2K≤70m.
Operation Temperature	0 ~ +40℃
Storage Temperature	-10 ~ +55℃

---

General	
Relative Humidity	10% ~ 90%
External Power Supply	100V-240V AC
Power Consumption	45W (Max)
Dimension (W*H*D)	436.4mm x 44mm x 276.5mm
Net Weight	3.17Kg

## 10. Panel Drawing



## 11. Troubleshooting & Maintenance

Problems	Potential Causes	Solutions
Output image with white noise.	Bad quality of the connecting cable	Try another high quality cable.
	Fail or loose connection	Make sure the connection is good
No output image when switching	No signal at the input / output end	Check with oscilloscope or multimeter if there is any signal at the input/ output end.
	Fail or loose connection	Make sure the connection is good.
	The switcher is broken	Send it to authorized dealer for repairing.
<b>POWER</b> indicator doesn't work or no respond to any operation	Fail connection of power cord.	Make sure the power cord connection is good.
Cannot control the device by control device (e.g. a PC) through RS232 port	Wrong RS232 communication parameters	Type in correct RS232 communication parameters.
	Broken RS232 port	Send it to authorized dealer for checking.

If your problem persists after following the above troubleshooting steps, seek further help from authorized dealer or our technical support.

## 12. After-Sales Service

If there appear some problems when running the product, please check and deal with the problems referring to this user manual. Any transport costs are borne by the users during the warranty.

**1) Product Limited Warranty:** The product will be free from defects in materials and workmanship for **two years** (The purchase invoice shall prevail).

Proof of purchase in the form of a bill of sale or receipted invoice which is evidence that the unit is within the Warranty period must be presented to obtain warranty service.

**2) What the warranty does not cover (servicing available for a fee):**

- Warranty expiration.
- Factory applied serial number has been altered or removed from the product.
- Damage, deterioration or malfunction caused by:
  - Normal wear and tear.
  - Use of supplies or parts not meeting our specifications.
  - No certificate or invoice as the proof of warranty.
  - The product model showed on the warranty card does not match with the model of the product for repairing or had been altered.
  - Damage caused by force majeure.
  - Servicing not authorized by distributor.
  - Any other causes which does not relate to a product defect.
- Delivery, installation or labor charges for installation or setup of the product.

**3) Technical Support:** For any questions or problems, contact your distributor or reseller and tell them the respective product name and version, the detailed failure situation as well as the formation of the cases.

## Asking for Assistance

**Technical Support:**

Phone: +49 5971 800299 - 0

Fax: +49 5971 800299 – 99

**Technical Support Hours:**

8:30 AM to 5:00 PM Monday thru Thursday

8:30 AM to 4:00 PM Friday

**Write to:**

PureLink GmbH

Von-Liebig-Straße 10

D - 48432 Rheine

[www.purelink.de](http://www.purelink.de)

[info@purelink.de](mailto:info@purelink.de)

---