



TICW401

4" 25/70/100V SHALLOW DEPTH IN CEILING/IN WALL 2-WAY
POWERED BY SONIC VORTEX®

Performs great as a combo audio speaker and paging speaker. Our Sonic Vortex® technology generates rich, deep bass and effortless clarity from what most people would call a 'back box', but is not. It is actually a compact, integrated tuned enclosure. This patented technology is a 'twist' on Ported Transmission Line design, that optimizes air movement to produce astonishing sound. The enclosure also keeps sound from bleeding to other rooms while adding 6 to 9dB boost in mid-lower bass. Designed to play in full range mode only. Versatile - both round and square grilles included.



Optional EZBracket pre-construction bracket;
use size "B" for this model.

- Woofer: 4" Fluted Reinforced Polymer
- Frequency/Crossover Setting: Full Range Mode Only
- Tweeter: 3/4" Aluminum Dome
- Surround: Butyl Rubber
- Coaxial Tweeter Design
- 25V Taps: 1.8, 0.9, 0.5, 0.3, 0.2 Watts
- 70V Taps: 15, 7.5, 3.8, 1.9, 1 Watts
- 100V Taps: 15, 7.5, 3.8, 1.9 Watts
- Low Impedance Bypass: 8Ω
- Power Handling (8Ω): 5-80W
- Speaker Weight: 2.59lbs (1.175 kg)
- Cutout: 6.4" (162 mm)
- Grille Diameter: 7.4" (186 mm)
- Depth: 3.82" (97 mm)
- Installed Frequency Response: 68 Hz - 20 kHz
- Sensitivity: 89 db
- Grille: Magnetic Bezelleless; White - Paintable
- Connector Type: Push Terminals
- Pre-construction Bracket: EZBracket Size: J



TICW401 Tap

Multiple International Patents Awarded
Additional Patents Pending

