

# Commercial Display


Model Name: ND75CMA

Taking simplicity, safety and flexibility to new levels. MAXHUB Commercial Display makes every organization more effective and productive.




### Professional 4K Display

4K Resolution  
Anti-Glare, 25% Haze



### Wireless Screen Sharing

Share your screen through MAXHUB  
Share app or wireless dongle




### External Control

Display Control through IP  
or RS232 protocol




### Device Management

Manage through cloud based  
MAXHUB Pivot



### Built-in Speakers

2 × 10W Dual speakers



### Upgrade Your Display

OPS slot availability to transform your  
display into a windows-based display



### Conformal Coating

Commercial level design of  
hardware



### Energy Saving

ErP Certified  
Energy Star 8.0 Certified



Display	
Screen Size (class)	75"
Diagonal	74.5" 189.3cm
Panel Type	ADS
Haze	25% (Anti-Glare)
Aspect Ratio	16:9
Native Resolution	3840 × 2160
Refresh Rate	60Hz
Brightness (Typ.)	500 nits
Backlight Type	DLED
Contrast Ratio	1,200:1 (Typ) 1,000,000:1 (Dynamic)
Viewing Angle (H × V)	178°
Response Time	8ms
Life Time (Min.)	≥50,000 hours
Operation Hours (Hours / Day)	18 / 7
Orientation	Portrait / Landscape

Internal Player	
Processor	A55 × 4
Graphic	Mali-G52 × 2
Memory	4G
Storage	32G
Operating System	Android 11.0
UI Resolution	4K

Connectivity		
Input	HDMI IN × 3	Up to 4K@60Hz, HDCP 2.1, CEC, ARC (HDMI 1)
	USB 2.0 × 1	For system upgrades
	USB 3.0 × 1	For external peripherals
	USB Type-C × 1	Video, Audio, PD 65W, LAN Network Sharing
		BYOD supported
Output	RS232 × 1	Baud rate 9600
	RJ45 IN × 1	10M / 100M / 1000Mbps
	HDMI OUT × 1	Up to 4K@60Hz, Follow HDMI IN, Type-C and OPS channel
	AUDIO OUT × 1	Android and HDMI 3 channel do not support
	SPDIF × 1	3.5mm Phone Jack
OPS Slot	RJ45 OUT × 1	PCM output format
		10M / 100M / 1000Mbps
Wi-Fi Slot		Module slot × 1
Wi-Fi		Wi-Fi 6 supported
Bluetooth		802.11ac/b/g/n/a/ax, 2.4GHz/5GHz

Environmental Conditions	
Operation Temperature	0℃ ~ 40℃
Operation Humidity	10% ~ 90%RH
Storage Temperature	-20℃ ~ 60℃
Storage Humidity	10% ~ 90%RH




Mechanical Specification	
Bezel Width (L × R × T × B)	15.9 / 15.9 / 15.9 / 15.9 mm 0.63 / 0.63 / 0.63 / 0.63 inch
Product Dimension (W × H × D)	1685.6 × 963.7 × 81.6 mm 66.36 × 37.94 × 3.21 inch
Package Dimension (W × H × D)	1863 × 1090 × 225 mm 73.35 × 42.91 × 8.86 inch
Product Weight (Net)	34.65 kg / 76.40 pounds
Package Weight (Gross)	48.15 kg / 106.15 pounds
VESA Mount (mm)	800 × 600
Handle	Yes

Power	
Power Supply	100-240V~50/60Hz
Power Consumption (Typical)	235W
Power Consumption (Max)	425W

Sound	
Speaker Power Output	2 × 10W

Certification	
Safety	IEC 62368-1
EMC	Class B
Energy Star	Yes
ErP	Yes

Feature	
Screen Share	MAXHUB Share Support BYOM / Miracast / Airplay / Chromecast
Device Management	MAXHUB Pivot
Protocol Control	RS232 / IP control
Special Features	Auto signal change / Built-in media player / Channel memory / Auto-rotate screen

Accessory	
Included in the package	Power Cord × 1 HDMI Cable × 1 Wi-Fi Module × 1 Remote Control × 1 Wall Mount × 1
Optional	<div> OPS (OPS62A)</div> <div> Mobile Stand (ST41B)</div> <div> Mobile Stand (ST23C)</div>

Warranty	
Display	3 years warranty