

Commercial Display


Model Name: ND98CMA

Taking simplicity, safety and flexibility to new levels. MAXHUB Commercial Display makes every organization more effective and productive.




Professional 4K Display

4K Resolution
Anti-Glare, 25% Haze



Wireless Screen Sharing

Share your screen through MAXHUB
Share app or wireless dongle




External Control

Display Control through IP
or RS232 protocol




Device Management

Manage through cloud based
MAXHUB Pivot



Built-in Speakers

2 × 10W Dual speakers



Upgrade Your Display

OPS slot availability to transform your
display into a windows-based display



Conformal Coating

Commercial level design of
hardware



Energy Saving

ErP Certified
Energy Star 8.0 Certified

Display	
Screen Size (class)	98"
Diagonal	97.5" / 247.7cm
Panel Type	ADS
Haze	25% (Anti-Glare)
Aspect Ratio	16:9
Native Resolution	3840 × 2160
Refresh Rate	60Hz
Brightness (Typ.)	500 nits
Backlight Type	DLED
Contrast Ratio	1,200:1 (Typ) 1,000,000:1 (Dynamic)
Viewing Angle (H × V)	178°
Response Time	8ms
Life Time (Min.)	≥ 50,000 hours
Operation Hours (Hours / Day)	24 / 7
Orientation	Portrait / Landscape

Internal Player	
Processor	A55 × 4
Graphic	Mali-G52 × 2
Memory	4G
Storage	32G
Operating System	Android 11.0
UI Resolution	4K

Connectivity		
Input	HDMI IN × 3	Up to 4K@60Hz, HDCP 2.1, CEC, ARC (HDMI 1)
	USB 2.0 × 1	For system upgrades
	USB 3.0 × 1	For external peripherals
	USB Type-C × 1	Video, Audio, PD 65W, LAN Network Sharing
		BYOD supported
Output	RS232 × 1	Baud rate 9600
	RJ45 IN × 1	10M / 100M / 1000Mbps
	HDMI OUT × 1	Up to 4K@60Hz, Follow HDMI IN, Type-C and OPS channel
	AUDIO OUT × 1	Android and HDMI 3 channel do not support 3.5mm Phone Jack
	SPDIF × 1	PCM output format
OPS Slot	RJ45 OUT × 1	10M / 100M / 1000Mbps
Wi-Fi Slot		Module slot × 1
Wi-Fi		Wi-Fi 6 supported 802.11ac/b/g/n/a/ax, 2.4GHz/5GHz
Bluetooth		5.2

Environmental Conditions	
Operation Temperature	0℃ ~ 40℃
Operation Humidity	10% ~ 90%RH
Storage Temperature	-20℃ ~ 60℃
Storage Humidity	10% ~ 90%RH

Mechanical Specification	
Bezel Width (L × R × T × B)	26 / 26 / 26 / 26 mm
	1.02 / 1.02 / 1.02 / 1.02 inch
Product Dimension (W × H × D)	2212.9 × 1268.4 × 79.4 mm 87.12 × 49.94 × 3.13 inch
Package Dimension (W × H × D)	2360 × 1425 × 280 mm 92.91 × 56.10 × 11.02 inch
Product Weight (Net)	69.90 kg / 154.10 pounds
Package Weight (Gross)	90.8 kg / 200.2 pounds
VESA Mount (mm)	800 × 600

Power	
Power Supply	100-240V~50/60Hz
Power Consumption (Typical)	340W
Power Consumption (Max)	515W

Sound	
Speaker Power Output	2 × 10W

Certification	
Safety	IEC 62368-1
EMC	Class B
ErP	Yes
Energy Star	Yes

Feature	
Screen Share	MAXHUB Share Support BYOM / Miracast / Airplay / Chromecast
Device Management	MAXHUB Pivot
Protocol Control	RS232 / IP control
Special Features	Auto signal change / Built-in media player / Channel memory / Auto-rotate screen

Accessory	
Included in the package	Power Cord × 1 HDMI Cable × 1 Wi-Fi Module × 1 Remote Control × 1 Wall Mount × 1
Optional	<div><div>OPS (OPS62A)</div><div>Wireless Dongle (WT13)</div><div>Mobile Stand (ST41B)</div><div>Mobile Stand (ST23C)</div></div>

Warranty	
Display	3 years warranty