

# MAXHUB 92" COMMERCIAL DISPLAY ULTRA-WIDE SERIES

Ultra Immersive Vision



Portrait /Landscape Mode







**ரீ** Empowered by Microsoft Teams Rooms

### MEETING WITHIN THE MEETING

Empowered by the Signature Microsoft Teams Rooms, the MAXHUB UW Series brings us a more immersive hybrid meeting experience.



### **IDEAL PLATFORM TO PERFORM**

This next-generation display is enhanced to be compatible with all the leading industry collaboration software. Invigorate every interchange with smoother, more engaging meetings.











# **EXPANSIVE VISION**

Ultra-wide, ultra-unique aspect ratio with 33% more visual canvas than comparable models



\*Only available for screensharing.

# **PROFESSIONAL 5K DISPLAY**

Keep an eye on all the details with a striking 5K-resolution display.





C 5K Carefully engineered to optimize the each plank 5K carefully engineered to optimize the each plank 5K careful luministic tests. Page 10 plank 10 plank







DEPENDABLE CHOICE FOR COMMERCIAL APPLICATIONS

Trust in the dependable choice that provides consistent and stable 24/7 performance.





TYPE-C VERSATILITY

Interchange ideas, power up productivity and share more content with the multi-functional Type-C port.

#### **DESIGNED FOR DIVERSE FUNCTIONALITY**

The panoramic viewing angle, large size, and 5K definition blend together to create a display that seamlessly matches the demands of hybrid working, commercial display, command & control, and a host of other professional situations.







HYBRID WORKING



COMMERCIAL DISPLAY



COMMAND AND CONTROL



# COMPLETE REMOTE DEVICE CONTROL

Easy-to-use functionality compatible with major control and automation tools offered by companies such as Crestron, Q-SYS and Extron.



#### SET-UP FOR BYOM

This is the ultimate package for collaborative meetings. Simply connect and play with automatic activation of the device's screen and external audio/video devices. The 2×20W+20W built-in speakers support a 2.1 channel configuration, revitalizing content sharing for maximum impact.



# MAXHUB DEVICE MANAGEMENT

MAXHUB Pivot equips a streamlined remote control device management system. Smooth, fuss-free interactions every time.



# **WIRELESS SHARING**

Elevate collaboration with instant device-to-screen sharing using the MAXHUB Share App, allowing up to nine devices to share screens simultaneously and enhance productivity.

# **SPECIFICATION**

# MAXHUB 92" COMMERCIAL DISPLAY ULTRA-WIDE SERIES

Display	
Model	UW92NA
Screen Size (Inch)	92
Aspect Ratio	21:9
Panel	VA
Backlight	DLED
Brightness	600 nits
Haze	25%
Resolution	5120 × 2160
Refresh Rate	60 Hz
Contrast Ratio	5000:1 (typ.) 1,000,000:1 (dynamic)
Viewing Angle (H / V)	178° / 178°
Display Orientation	Landscape / Portrait
Operation Hours (Hours / Day)	24 / 7
Response Time	6.5 ms
Life Time (50%)	>50,000 hours
Built-in System	
Operating System	Android 13.0
CPU	A76 × 4 + A55 × 4
GPU	Mali-G610 MP4
RAM	8 GB
ROM	64 GB
System OS	MAXHUB Meeting OS V6

Screen share	MAXHUB Share Support BYOM / Miracast Airplay / Chromecast
Device Management	MAXHUB Pivot
Protocal Control	RS232 / IP control
Special Features	Screen rotation / Auto input change / Play via URL Wake on LAN / HDMI CEC Compatible with control systems (Crestron, Q-SYS, and Extron)
Connectivity	
Input	HDMI IN × 4 HDMI 20 × 3, HDMI 2.1 × 1 USB 2.0 × 1 USB 3.0 × 4 USB Type-C × 1 DP IN × 1 AUDIO IN × 1 RS232 × 1 RJ45 IN × 1
Output	HDMI OUT × 1 TOUCH 2.0 × 3 AUDIO OUT × 1 SPDIF × 1 RJ45 OUT × 1
OPS Slot	Module slot × 1
Wi-Fi	Wi-Fi 6

Bluetooth	5.2
Audio	
Sound Channel	2.1
Speaker Power	2 × 20W + 20W
Power	
Power Supply	100-240V~50/60Hz
Power Consumption (Energy Saving)	177 W
Power Consumption(Typ.)	320 W
Power Consumption(Max.)	530 W
Physical Specification	
Bezel Width $(L \times R \times T \times B)$	17.9 / 17.9 / 17.9 / 17.9 mm 0.7 / 0.7 / 0.7 / 0.7 inch
$Dimension(W \times H \times D)$	2182 × 944 × 85 mm 85.90 × 37.16 × 3.35 inch
Shipping Dimension(W $\times$ H $\times$ D)	2360 × 1072 × 225 mm 92.91 × 42.20 × 8.86 inch
VESA	800 × 600 mm
Net Weight	43.40 Kg
Gross Weight	62.60 Kg
Environmental Conditions	
Operating Temperature	0°C ~ 40°C
On another Hamilton	

Storage Temperature	-20°C ~ 60°C
Storage Humidity	10% ~ 90%RH
Certification	
Energy Star	
IP Rating	IP5X
Warranty	
Display	3 years warranty
Accesories	
Power Cord	
HDMI Cable	
Remote Control	
Wall Mount	
Wireless Adapter	
Optional Module	
OPS	OPS72A
Mobile Stand	ST41B ST23C
Wireless Dongle	WITE:









